

Automatic unsealing-dehydrating unit
for chicken package

AIR-2K Air Kei



The cutting edge
nantsune

Unseal



Remove



Dehydrate



... Still done by hand ? ...

Support saving your cost! By automating all process !



Dehydrating machine



Unsealing machine



For food processing

Nantsune Co., Ltd.

Unseal and dehydrate mass chicken packages with preventing from contamination

Automatic unsealing-dehydrating unit for chicken package

Air Kei
AIR-2K

Automatic feeding

Load material by conveyor and proceed dehydrating automatically.



Low contamination risk

Hold package by clumping unit and unseal by stainless blade with replenishing clean air inside.



Automatic discharging unsealed package

Discharge unsealed package to dust bag. Store it with small volume by pressing it with arm.



Automatic dehydrating

Automatically remove drip both in front and rear material surface with 2 steps dehydrating conveyors.



For more automation and efficiency

More automating and streamlining is available by combining with following process such as dice cutting and deli producing.



Easy operation

Only setting replenishing air amount and opening time of bottom door are necessary to set up for operation. Memory function for several package types is available.



■ Specification

Dimensions	Unsealing《A》	: W1800 × L1910 × H1550 mm
	Dehydrating《B》	: W1490 × L1660 × H1452 mm
	《A+B》	: W2800 × L2806 × H1550 mm
Weight	Unsealing《A》	: 400 kg
	Dehydrating《B》	: 300 kg
	《A+B》	: 700 kg
Power	3ph 200V	50/60Hz 15A
Rating	Unsealing	: 180 W
	Dehydrating	: 270 W
Capacity	Feeding conveyor	: 90 W
	Loading conveyor	: 90 W
	Receiving conveyor	: 90 W
	Dehydrating conveyor	: 90 W × 2
Production capacity	MAX 900 Packages/hr	
Loaded weight	2 kg	
Loading temperature	0°C~4°C	
	※Depends of material.	
Air pressure	0.6 Mph 810 ℓ/min	Tube Diameter : 12 mm
	※Optional compressor available.	

■ Dimensions (Unit:mm)

